

| ITEM CODE | | | | RATED CURRENT | RATED VOLTAGE | ITEM DESCRIPTION |
|-----------|----------|--------------|-------------|---------------|---------------|-------------------|
| White | Cream | Gun Metallic | Black Matte | | | |
| 260-0110 | 260-0111 | 261-0111 | 261-0112 | 10AX | 250V~ | 1Gang 1Way Switch |
| 260-0210 | 260-0211 | 261-0211 | 261-0212 | 10AX | 250V~ | 1Gang 2Way Switch |
| 260-0120 | 260-0121 | 261-0121 | 261-0122 | 10AX | 250V~ | 2Gang 1Way Switch |
| 260-0220 | 260-0221 | 261-0221 | 261-0222 | 10AX | 250V~ | 2Gang 2Way Switch |
| 260-0130 | 260-0131 | 261-0131 | 261-0132 | 10AX | 250V~ | 3Gang 1Way Switch |
| 260-0230 | 260-0231 | 261-0231 | 261-0232 | 10AX | 250V~ | 3Gang 2Way Switch |
| 260-0140 | 260-0141 | 261-0141 | 261-0142 | 10AX | 250V~ | 4Gang 1Way Switch |
| 260-0240 | 260-0241 | 261-0241 | 261-0242 | 10AX | 250V~ | 4Gang 2Way Switch |

APPLICATIONS

Residential/Hotel/General Purpose

PRODUCT SPECIFICATIONS

| | |
|--------------------------------|--|
| Method of Application | : Flush type |
| Method of connecting cables | : Rewireable |
| Type of Terminals | : Screw type |
| Method of Installation | : Fixed |
| Mounting Center Distance | : 60.3mm |
| Recommended Mounting Box Depth | : 35mm |
| Warranty Period | : Lifetime warranty* |
| Standard Complied | : IEC 60669 BS EN 60669 IS 3854 SLS 1000 |
| Materials | : Plastics: Polycarbonate & Nylon (Flame Retardant) Metal Parts: Brass & Copper Contacts: Pure Silver & Silver Cadmium |

