

# Product data sheet

## Characteristics

# E8231BPDMW\_WE

10A 250V 1G Bel SW w Illu "Pvc", "Pls CleanUp"  
& "Pls Wait" Sym, White



### Main

Range	Pieno
Product or component type	Switch
Switch application	Control switch Bell switch
Load type	Fluorescent Resistive
Cover frame colour tint	White

### Complementary

Wiring device mounting	Surface Flush
Device mounting	Flush Surface
Switch function	Switch
Rated current	10 A at 250 V AC 50 Hz
Local signalling	Please wait, neon (orange) Please clean up, neon (green) Privacy, neon (red)
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	By screw
Clamping connection capacity	1 x 2.5 mm <sup>2</sup> for solid cable(s) 1 x 1.5 mm <sup>2</sup> for stranded cable(s)
Embedding depth	21 mm
Width	87 mm
Height	87 mm
Depth	35.5 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1 GB 16915.1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	111 g
Package 1 Height	3.6 cm
Package 1 width	8.7 cm
Package 1 Length	8.7 cm

## Contractual warranty

Warranty	18 months
----------	-----------