

10kA

4 POLE ISOLATOR			
ITEM CODE	RATED CURRENT	NO. POLES	RATED VOLTAGE
513-2007	40A	4	400V
513-2008	63A	4	400V
513-2009	100A	4	400V

APPLICATIONS

Industrial/Residential/Hotel/General Purpose

PRODUCT SPECIFICATIONS

Connection	: Screw type terminals
Method of Installation	: Mounting on 35mm DIN rail
Warranty Period	: Lifetime warranty*
Standard Complied	: IEC 60947-3
Suitability for Isolation	: Suitable
Utilization Category	: AC-22A
Kind of Current	: a.c.
Rated Frequency	: 50Hz
Rated Operational Voltage (Ue)	: 400VAC - (4P)
Rated Insulation Voltage (Ui)	: 690V
Rated Impulse withstand Voltage (Uimp)	: 6kV
Rated Operational Current (Ie)	: 40, 63, 100A
Conventional Free Air Thermal Current(Ith)	: 40, 63, 100A
Rated Uninterrupted Current (Iu)	: 40, 63, 100A
Rated Short Time withstand Current (Icw)	: 12Ie, 1s
Rated Short Circuit Making Capacity (Icm)	: 20 Ie
Degree of Protection	: IP 20
Temperature Limit	: -25 °C to + 40 °C

